

ARGuard™ Full Synthetic GL-5 Gear Oil 75W-90

PROD. CODE
7767

ARGuard™ Full Synthetic GL-5 Gear Oil 75W-90 is formulated with synthetic base stocks and premium additives to provide improved extreme pressure protection under high load operation. Excellent fluidity at low temperatures assures faster lubrication of components and easier shifting of transmissions. Prevent corrosion and rusting of transmission and differential components.

ARGuard™ Full Synthetic GL-5 Gear Oil 75W-90 has an improved thermal stability at high temperatures resulting in less deposit formation and better compatibility with seals. This oil provides the potential for improving fuel economy and extending drain interval.

FEATURES & BENEFITS

- Exceptional thermal and oxidation stability
- Excellent seal compatibility
- Extended drain capabilities with exceptional axle wear protection under the high temperature conditions demanded by passenger car OEMs for towing and off-road application
- Outstanding anti-foam protection
- Made with synthetic base stocks that naturally give high viscosity index and low pour point, it provides extremely broad operating temperature ranges when compared with conventional mineral oil based gear lubricants.
- Protection durability as defined by the ASTM L37 test

INDUSTRY & OEM SPECIFICATIONS

- API GL-5 and MT-1
- SAE J2360¹

APPLICATIONS²

ARGuard™ Full Synthetic GL-5 Gear Oil 75W-90 is recommended for domestic and imported year-round use in heavy duty commercial vehicle axles, non-synchronized manual transmissions, passenger car axles and transfer cases that require an API GL-5 or MT-1 gear oil.

METHOD	DESCRIPTION	TYPICAL
D445	VISCOSITY @ 100°C, cSt	16.70
D4052	SPECIFIC GRAVITY @ 60°F	0.851
D5950	POUR POINT, °C	-48
D92	FLASH POINT, °C	190
D1500	COLOR ASTM	L1.0
D2983	BROOKFIELD VISCOSITY, mPa s (cP)	91,000 (-40°C)
D130	COPPER CORROSION	1B

1. Meets the requirements of this standard and it is capable of being approved

2. Always follow operator's manual to confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's practices

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

 **AMERICAN
REFINING
GROUP, INC.**
Refine everything.™