

ARGuard™ Multi-Vehicle ATF

PROD. CODE
7419

ARGuard™ Multi-Vehicle ATF offers extended friction control protection that lasts over the life of the fluid-long after the anti-shudder protection found in many competitive brands. Made with full synthetic base stocks, this high viscosity Multi-Vehicle ATF is inherently more thermally stable when compared with conventional base stocks.

ARGuard™ Multi-Vehicle ATF is designed for use in most modern passenger vehicles and heavy duty applications. It also can be used in applications where its performance features exceed the requirements of older specifications.

FEATURES & BENEFITS

- Full synthetic formula with outstanding low temperature performance
- Improved wear performance and reduced oil consumption
- Provides extended anti-shudder performance for smooth driving
- Excellent oxidation and thermal stability
- Exceeds the most demanding JASO 1A performance standard

APPLICATIONS

ARGuard™ Multi-Vehicle ATF is a high viscosity fluid specially formulated to exceed the performance and protection requirements of newer transmissions. Installers can rely on this single fluid to conveniently and accurately meet a wide array of global OEM requirements in North America as the ones listed on the table above.

METHOD	DESCRIPTION	TYPICAL
Calculated	API GRAVITY	34.2
D445	VISCOSITY @ 40 °C, cSt	36.26
D445	VISCOSITY @ 100 °C, cSt	6.90
D2270	VISCOSITY INDEX	153
D5950	POUR POINT, °C	-54
D2983	BROOKFIELD @ -40 °C, cP	19,000

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200



INDUSTRY & OEM SPECIFICATIONS

OEM	APPLICATION	OEM	APPLICATION	OEM	APPLICATION	OEM	APPLICATION	
ALLISON	C4	Mercedes / Daimler	MB 236.5	Hyundai / Kia	P/N UM040 CH20 Red-1	Porsche	P/N 000 043 204 41	
	TES-295 ^a		MB 236.6		SP-II		P/N 000 043 205 09	
	TES-389		MB 236.7		SP-III		P/N 000 043 205 28	
ATF	Esso LT 71141		MB 236.8	Idemitsu	ATF HP		PSA Peugeot Citroën	P/N 999 917 547 00 (A2)
	JWS 3309		MB 236.9		K17	P/N Z 000169756		
	Mobil ATF 3309		MB 236.91	Isuzu	ATF II	Renault	Matic D2	
	Shell 3403-M115		Ford / Lincoln / Mercury		P/N XT-2-QDX [M]		ATF III	Renk
	Shell LA 2634				P/N XT-2-QSM [Syn]	Genuine ATF	Saab	3309 - T -IV
	Texaco ETL 7045E	P/N XT-5-QM or -DM [V]		P/N 08200-9001	SSANY YONG	DSIH 5M-66		
	Texaco ETL 8072B	P/N XT-8-QAW [Premium]		Jaguar	JLM 20238	Subaru	HP	
Texaco ETL N402	P/N XT-9-QMM5 [FRN5]	JLM 20292	P/N K0140Y0700					
BMW / MINI	P/N 81 22 9 400 272/275	WSS-M2C922-A1	JASO		JLM 21044	Suzuki	3314	
	P/N 81 22 9 407 858/859	GM / GMC / Opel / Saturn		K17	3317			
	P/N 83 22 0 024 249/359			II	Toyota / Lexus / Scion	Type D-II		
	P/N 83 22 0 026 922			IID		Type T		
	P/N 83 22 0 402 413		III	Type T-III				
	P/N 83 22 0 403 248		IIIE	Type T-IV				
	P/N 83 22 0 403 249		IIIG	Mazda	F-1	Volkswagen / Audi	G 052 025 A2	
	P/N 83 22 7 542 290	IIIH	JWS3317		G 052 055			
	P/N 83 22 9 407 765	P/N 12378515 [Synthetic]	M-5, P/N XT-9-QMM5	G 052 162 (-A1, -A2)				
	P/N 83 22 9 407 807	P/N 19 40 700	M-III	G 052 990 (A2)				
Chrysler / Dodge / Jeep	+	P/N 19 40 767	MAN	Type T-IV	Volvo	P/N 1161521		
	+2	P/N 21005966 Transaxle		339A		G 052 162 (-A1, -A2)		
	+3	P/N 22717466		Mitsubishi		ATF-J2	G 055 025 (A2)	
	+4 ^a	P/N 88900925	SP, P/N MS991156		G US 000 162			
	AS68RC ATF	P/N 9986195	SP-II		Volvo Constr. Equip. (VCE)	1273, 4		
	SP-III	T-IV	SP-III	P/N 1161540 / 1161640				
Mercedes / Daimler	MB 236.10	Honda / Acura	Z-1	Nissan / Infinity	402	ZF	TE-ML 11A	
	MB 236.11		ATF Red-1K		Matic-D		TE-ML 11B	
	MB 236.3		Genuine ATF		Matic-J			
			JWS-3309 T-4		Matic-K			
					Matic-W			

Consult your owner's manual regarding its suitability as ATF in imported vehicles. Do not use in ATF applications where CVT fluids or Ford ATF Type F is required. Do not use in Honda power steering fluid systems.

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

