

ARGuard™ Premium Universal Tractor Fluid

PROD. CODE
7352

ARGuard™ Premium Universal Tractor Fluid is a proven high quality universal tractor fluid for use in transmissions, final drives and hydraulic systems for most major brands of agricultural and construction equipment. ARGuard™ Premium Universal Tractor Fluid is formulated with the latest additive technology to provide maximum protection for equipment employing a common fluid reservoir.

FEATURES & BENEFITS

- Superior water tolerance and low temperature fluidity provides protection in all working environments
- Meets or exceeds the performance requirements of both hydraulic and transmission fluid systems for major agricultural and construction equipment
- Prevents grabbing or chattering of wet brakes and PTO clutches

APPLICATIONS

ARGuard™ Premium Universal Tractor Fluid is specially formulated to meet or exceed the performance and protection requirements of most North American agricultural and construction equipment

METHOD	DESCRIPTION	TYPICAL
Calculated	DENSITY, LBS/GAL	7.276
D4052	API GRAVITY	30.7
D445	VISCOSITY @ 40 °C, cSt	59.46
D445	VISCOSITY @ 100 °C, cSt	9.62
D2270	VISCOSITY INDEX	145
D2983	BROOKFIELD VISCOSITY, cP @ -20 °C	3,760
D2983	BROOKFIELD VISCOSITY, cP @ -35°C	54,100
D1500	COLOR	L2.5
D5949	POUR POINT, °F (°C)	-33 (-36)
D92	FLASH POINT, °F (°C)	430 (221)

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200



ARGuard™ Premium Universal Tractor Fluid

PROD. CODE
7352

INDUSTRY & OEM SPECIFICATIONS

OEM	APPLICATION	OEM	APPLICATION
AGCO	Allis Power Fluid 821 XL	John Deere	JDM J20C
	Allis Chalmers Power Fluid 821	Komatsu Dresser	B-06-0001
	Massey-Ferguson M-1135, M-1141, M-1145		B-06-0002
	White Farm Q-1826	Kubota	UDT
Allison	C-3 and C-4	Sperry Vickers	I-286-S
Caterpillar	TO-2		M-2950-S
Dennison	HF-0, HF-1 & HF-2	Volvo	WB-101
CNH Global N.V.	MAT 3525/FNHA-2-C-201	ZF	TE-ML 03E
	MAT 3505/MS 1209		TE-ML 03F
	MAT 3526		TE-ML 05F
	MS-1206, MS-1210		TE-ML 06K

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

