

Kendex[®] 0100

PROD. CODE
4306

This 100 SUS solvent neutral base oil is often used in rubber processing or as a diluent or carrier fluid.

FEATURES & BENEFITS

- Low sulfur
- Provides good viscosity
- Good solvency
- Low temperature fluidity

REGULATORY

Meets 21 CFR 178.3620(c) mineral oil as component of non-food articles intended for use in contact with food (FDA regulations)

APPLICATIONS

Metalworking, automotive, diluent oil, process oil, industrial coatings, carrier fluid

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
D4052	API GRAVITY			33.1
D4052	LB/GAL			7.17
D445	VISCOSITY @ 40°C, cSt	18.3	20.2	19.0
D445	VISCOSITY @ 100°C, cSt			4.0
D2270	VISCOSITY INDEX			100
D6045	COLOR, ASTM		1.0	0.5
D97	POUR POINT, °C		-9	-15
D92	FLASH POINT, °F	335		395 (202°C)

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

