

# Kendex<sup>®</sup> 0200

PROD. CODE  
4300

This 200 SUS solvent neutral base oil blend is utilized in process oils including rubber and plasticizer applications.

## FEATURES & BENEFITS

- High viscosity index
- High flash point
- Low pour point

## APPLICATIONS

Metalworking, rubber and plasticizer applications

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
D4052	API GRAVITY			30.9
D445	VISCOSITY @ 40°C, cSt	39.0	42.0	40.7
D445	VISCOSITY @ 100°C, cSt			6.35
D2270	VISCOSITY INDEX			104
D92	FLASH POINT, °F	380		440
D5949	POUR POINT, °C		-9	-12
D1500	COLOR			3.0

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

