

# Kendex<sup>®</sup> 0325D

PROD. CODE  
4324

This 325 SUS solvent neutral base oil blend is used in diluent oils and process oils including rubber and plasticizer applications. It is well suited as a blending stock for an ISO VG 68 hydraulic fluid.

## FEATURES & BENEFITS

- High viscosity index
- High flash point
- Low pour point

## APPLICATIONS

Hydraulic oils, diluent and carrier fluids, rubber process oils, plasticizers

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.29
D1298	API GRAVITY			30.2
D445	VISCOSITY @ 40°C, cSt	62.0	74.0	
D445	VISCOSITY @ 100°C, cSt			8.70
D2270	VISCOSITY INDEX			100
D92	FLASH POINT, °F (°C)	425 (218)		
D5949	POUR POINT, °C (°F)		-9 (16)	
D1500	COLOR			5.5

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

 **AMERICAN  
REFINING  
GROUP, INC.**  
Refine everything.™