

Kensol[®] 10

PROD. CODE
4102

Kensol[®] 10 is a naphtha blend, also known as white gas, that is highly refined and contains no impurities. Kensol[®] 10 is most notable for its use as a stove or lantern fuel.

FEATURES & BENEFITS

- Rapid ignition
- Burns brightly
- Low odor

APPLICATIONS

- Lantern & stove fuel
- Industrial & household cleaners

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
D4052	API GRAVITY	65		68
	LBS/GAL			5.90
D56	FLASH POINT, TCC, °F (°C)			< -10 (< -23)
D5949	POUR POINT, °C (°F)			< -57 (< -71)
D86	DISTILLATION, °F			
	IBP	100	135	113
	5%			144
	50%	200	235	224
	95%	300	340	330
	EBP		370	363
D5191	VAPOR PRESSURE, PSI	4.0	6.3	5.5
D7039	SULFUR, ppm			< 2
D4952	DOCTOR TEST	NEGATIVE/SWEET		
D130	COPPER STRIP CORROSION, 3HRS @ 122°F		1A	
D1133	KAURI BUTANOL VALUE			33.1
D611	ANILINE POINT, °C			61.5
D1319	FIA ANALYSIS, VOL %			
	AROMATICS			6.9
	SATURATES			92.4
D6729	BENZENE CONTENT, WT %			0.125
D6045/D156	COLOR, SAYBOLT			+30
OLFACTORY	ODOR			MILD PETROLEUM SOLVENT
	VISUAL			CLEAR & BRIGHT

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

 **AMERICAN
REFINING
GROUP, INC.**
Refine everything.™