

Kenwax® 0111 Petrolatum

PROD. CODE
4459

This 150°F melt point bright stock petrolatum is an intermediate component, frequently used in cosmetics, lotions and other ointments. It's also used to create products such as water repellents, sealants and polishes.

FEATURES & BENEFITS

- Consistent properties
- Excellent cohesive properties
- Good laminating strength
- Microcrystalline wax precursor

APPLICATIONS

Intermediate component in the production of cosmetics, lotions, and ointments, leather finishing, compounding of rubber, rust prevention, toilet bowl rings, cable filler, lubricants and more

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
D1298B	API GRAVITY			31.0
D92	FLASH POINT, °F	550		580
D88	VISCOSITY @ 210°F, SUS	75.0	112.0	
D445	VISCOSITY @ 100°C, cSt	16.0	24.0	20.0
D127	MELT POINT, DROP °F	142	160	148
D937	CONE PENETRATION @ 77°F, dmm		100	60
D721	OIL CONTENT, %	8	15	10.5
	SULFUR, WT %			0.04
D1500	COLOR, ASTM			8.0

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

