

Safety Data Sheet

Prepared according to GHS

1. Identification

Product Name Full Synthetic Motor Oil SAE 0W-20, 5W-30

Product Code(s) 7550, 7552 Recommended Use Engine Oil

Company American Refining Group, Inc.

77 North Kendall Avenue Bradford, PA 16701 www.amref.com msds@amref.com

Emergency Telephone Chemtrec 1-800-424-9300 (24 HRS)

Number(s) ARG: 814-368-1297 (24 HRS)

2. Hazards Identification

GHS Classification This product is not considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Signal WordNot applicableHazard StatementsNot applicableOther Hazard InformationNot applicableGHS PictogramNot applicablePrecautionary StatementsNot applicable

3. Composition / Information on Ingredients

CAS No.	Component	Common Name	Percent
This product does n	ot contain ingredients that are hazardous by	the OSHA Hazard Communic	cation Standard
_	(29 CFR 1910.1200)	

4. First Aid Measures

Eyes Check for and remove any contact lenses. Flush eyes with plenty

of water, occasionally lifting the upper and lower eyelids. Get

medical attention if irritation develops.

Skin In case of contact, flush skin with plenty of soap and water while

removing contaminated clothing and shoes. Wash clothing before

reuse. Get medical attention if irritation develops.

Inhalation Move exposed person to fresh air. Get medical attention if

irritation develops.

Ingestion First aid is normally not required. Get medical attention if

discomfort develops.

7550, 7552 Revision #:0 Page 2 of 7

4. First Aid Measures

Note to Physicians

No specific treatment. Treat symptomatically. Contact poison treatment specialist if large quantities have been ingested or inhaled.

5. Fire Fighting Measures

Suitable Extinguishing Media

Use dry chemical, CO₂, water spray (FOG) or foam

Unsuitable Extinguishing Media

Avoid solid water stream as it may scatter and spread fire.

Specific Hazards Arising from Chemical

Elevated temperatures can lead to the formation of irritating vapors. Decomposing products may include the following materials: Carbon dioxide and Carbon monoxide.

Protective Equipment and Precautions for Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release Measures

Personal Precautions

Put on appropriate personal protective equipment.

Environmental Precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas.

Methods for Containment

Stop leak if without risk.

Methods for Cleanup

Cover liquid spill with sand, earth or other noncombustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Pick up and transfer to properly labeled container

7. Handling and Storage

Handling Procedures

Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist.

Shipping and Storing Procedures

Keep container tightly closed in a dry place. Keep away from heat. Protect from light. Keep in properly labeled containers. Keep out of the reach of children.

Incompatibilities:

Oxidizing Agents

8. Exposure Controls / Personal Protection

Component Exposure Limits*

When mists/aerosols can occur the following are recommended: 5 mg/m³ - ACGIH TLV (inhalable fraction), 5 mg/m³ - OSHA PEL.

*Product has 0 kPa pressure at 68°F and is not expected to present any inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. Oil mist, if generated, is considered hazardous according to the OSHA Hazard Communication Standard.

7550, 7552

Revision #:0 Page **3** of **7**

8. Exposure Controls / Personal Protection

Engineering ControlsMaterial should be handled in enclosed vessels and equipment only if

aerosolized and/or misted. Use only in adequate ventilation if this occurs. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants

below any recommended or statutory limits.

Eye/Face Protection Safety glasses

Skin Protection Normal work gloves are appropriate

Respiratory ProtectionNo special requirements under ordinary conditions of use and with

adequate ventilation.

General Hygiene Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove

potentially contaminated clothing.

9. Physical and Chemical Properties

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Please see the Product Specification Sheet for further information.

Appearance	Amber	Flammability	Not available
Physical State		Upper/Lower	Not available
		Flammability Limits	
Odor	Petroleum	Vapor Pressure (kPa at	Not Available
		20°C)	
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density (lbs/gal)	7.09
Melting/Freezing Point	Not available	Water Soluble	No
(°F)			
Initial Boiling Point (°F)	Not available	Partition Coefficient: n-	Not available
		octanol/water	
Boiling Range (°F)	Not available	Auto-ignition	Not available
		Temperature (°F)	
Flash Point (°F)	>410	Decomposition	Not available
		Temperature (°F)	
Evaporation Rate	Not available	Viscosity (40°C mm²/s)	>40

10. Chemical Stability & Reactivity Information

ReactivityPolymerization will not occurChemical StabilityStable under normal conditionsHazardous ReactionsNone, under normal processing.

Conditions to Avoid High temperatures

Incompatibility Strong acids and oxidizing materials

Hazardous Decomposition Smoke, carbon monoxide, carbon dioxide, aldehydes and other

Products products of incomplete combustion.

11. Toxicological Information

vision #:0 Page 4 of 7

11. Toxicological Information

Respiratory Irritation Not expected to pose respiratory irritation. An inhalation hazard may only

arise if product is aerosolized or if heated up. If material is misted or if vapors

are generated from heating, exposure may cause irritation of mucous

membranes and upper respiratory tract. Based on data from similar materials.

Eye Irritation Contact with eyes may cause irritation. **Skin Irritation** May be harmful in contact with skin.

Sensitization Not expected to cause skin or respiratory sensitization. **Aspiration Hazards** Not expected to pose an aspiration hazard if swallowed.

Chronic Exposure

Target Organ EffectsNo data available to indicate product or components at greater than 1% are

chronic health hazards.

Mutagenicity No data available to indicate product or any components present at greater

than

.1% are mutagenic or genotoxic.

Reproductive ToxicityNo data available to indicate either product or components present at

greater

than .1% that may cause reproductive toxicity.

Carcinogenicity No data available to indicate product or any components present at greater

than .1% are carcinogenic.

Chemical Name	ACGIH	IARC	NTP	OSHA
Distillates (Petroleum)	A2	Group 1	Known	X
Hydrotreated Heavy Paraffinic				
64742-54-7				
Distillates (petroleum)	A2	Group 1	Known	X
Solvent-dewaxed Heavy				
Paraffinic				
64742-65-0				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2- Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1-Carcinogenic to Humans

NTP (National Toxicology Program)

Known- Known Carcinogen

OSHA (Occupational Safety and Health Administration)

X- Present

Component Analysis – LD50 / LC50

 Inhalation LC50 Rat
 >20 mg/L 4h

 Oral LD50 Rat
 >5000 mg/kg

 Dermal LD50 Rabbit
 >2000 mg/kg

12. Ecological Information

12. Ecological Information

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0		LC50: >5000mg/L (96h, Oncorhynchus mykiss)	\$ 4 .0	EC50: >1000mg/L (48h, Daphnia magna)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1		LC50: >5000mg/L (96h, Oncorhynchus mykiss)	\$ # .71	EC50: >1000mg/L (48h, Daphnia magna)
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	8 = 31	EC50: >1000mg/L (48h, Daphnia magna)
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	8 = 31	EC50: >1000mg/L (48h, Daphnia magna)
Zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate) 4259-15-8	EC50: 1.0 - 5.0mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 10.0 - 35.0mg/L (96h, Pimephales promelas) LC50: 1.0 - 5.0mg/L (96h, Pimephales promelas)	-	EC50: 1 - 1.5mg/L (48h, Daphnia magna)
Zinc O,O,O',O'-tetrakis(1,3-dimethylb utyl) bis (phosphorodithioate) 2215-35-2	EC50: 1.0 - 5.0mg/L (96h, Pseudokirchneriella subcapitata)	LC50: >100mg/L (96h, Pimephales promelas) LC50: 25 - 50mg/L (96h, Pimephales promelas)	-	EC50: 4.0 - 6.0mg/L (48h, Daphnia magna)

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate)	3.59
4259-15-8	
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis	2.21
(phosphorodithioate)	
2215-35-2	

Mobility in soil

Other adverse effects

No information available.

13. Disposal Considerations

Disposal Instructions

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

Page **6** of **7**

14. Transportation Information

Emergency Response Guide		171		North American Er	nergency Response	
No.				Guide Book		
	UN Number		ipping Name (technical ne)	H	Hazard Class	Packing Group
U.S. DOT Bulk		No	t Regulated			
U.S. DOT Non-Bulk		No	t Regulated			
IATA		No	t Regulated			
IMDG		No	t Regulated		_	

15. Regulatory Information

SARA Extremely Hazardous Substances (Sections 302 & 304) This product does not contain greater than 1% of any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B. This Product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of

SARA Section 313

Federal Regulations Part 372

SARA Section 311 & 312 Classifications

Health Hazard No **Physical Hazard** No

CERCLA This product does not contain any "hazardous substances" listed under the

Comprehensive Environmental Response, Compensation and Liability Act of

1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

California Prop 65 This product is not routinely tested to determine chemical(s) known to the

state of California to cause cancer and/or birth defects based on maximum

impurity levels of components.

Global Chemical Inventories

Inventory	
US TSCA	Listed
EU	Listed
Japan	Not available
Australia	Listed
New Zealand	Not available
Canada	Listed
Switzerland	Not available
Korea	Listed

Full Synthetic Motor Oil

7550, 7552 Revision #:0

American	Refining Group,	Inc.
	Page 7 of 7	

Philippines	Listed
China	Listed
Taiwan	Not available

1/	Δa	TC	4 •
16	()ther	Inform	ation
10.	Oulu		auvn

US NFPA Ratings

Health	Fire	Reactivity
0	1	0

HMIS Ratings

Health	Fire	Physical Hazards
0	1	0

Revision Date Revision Reason 21 April 2023 New SDS

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS