

# ARGuard™ Ashless Natural Gas Engine Oil

PROD. CODE  
7261, 7262

ARGuard™ Ashless Natural Gas Engine Oils are high performance, premium quality, ashless natural gas engine oils recommended for naturally aspirated and turbocharged two-stroke and certain select four-stroke engines. They are formulated with Group II base stocks and a carefully selected high performing additive package.

## FEATURES & BENEFITS

- Promotes low maintenance cost and long engine life
- Minimizes ash deposits
- Low ring and cylinder liner wear
- Minimum viscosity increase in severe service

## INDUSTRY & OEM SPECIFICATIONS

- Ajax
- Caterpillar (except 3400, 3500, 3600)
- Clark-Dresser
- Cooper Bessemer (two-stroke)
- Dresser-Rand (Ingersoll-Rand) Categories I and II
- Fairbanks-Morse/MEP
- Waukesha VT and Intermediate/Clinton
- Worthington (two-stroke)

## APPLICATIONS

ARGuard™ Ashless Natural Gas Engine Oils are recommended for all two-stroke and selected four-stroke stationary engines that require a completely ashless engine oil which use natural gas.

METHOD	DESCRIPTION	TYPICAL	
		40 (7261)	15W-40 (7262)
	LBS/GAL	7.34	7.25
D4052	API GRAVITY	29.1	31.4
D445	VISCOSITY @ 40 °C, cSt	119.3	108.8
D445	VISCOSITY @ 100 °C, cSt	12.8	14.1
D2270	VISCOSITY INDEX	100	131
D1500	COLOR	1.0	1.2.0
D5949	POUR POINT, °C	-21	-33
D92	FLASH POINT, °F	450	480
D2896	TBN	1.1	1.2
D874	SULFATED ASH, wt. %	<0.1	<0.1

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

