

# ARGuard™ Concrete Form Oil

PROD. CODE  
7705, 7706

ARGuard™ Concrete Form Oils are premium quality, non-staining releasing agents for metal and wooden forms. They are specially formulated to prevent cement from adhering to form surfaces.

## FEATURES & BENEFITS

- Light colored
- Non-drying oily film
- Resists water wash-off
- DOT approved\*

## APPLICATIONS

ARGuard™ Concrete Form Oils are designed for all temperatures and most all concrete molding operations. They are easy to apply, ready to use oils. Apply to a clean, dry surface with a roller, brush or sprayer.

\* Note: Please check federal, state and local VOC regulations

METHOD	DESCRIPTION	TYPICAL	
		65 SUS (7705)	95 SUS (7706)
	LBS/GAL	7.117	7.229
D4052	API GRAVITY	34.3	31.7
D445	VISCOSITY @ 40°C, cSt	11.0	21.7
D445	VISCOSITY @ 100°C, cSt	2.9	4.4
D2270	VISCOSITY INDEX	106	114
D1500	COLOR	L 1.0	1.5
D5949	POUR POINT, °C	-39	-42
D92	FLASH POINT, °F	355	390
EPA METHOD 24	VOC CONTENT	62	27

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

