

# ARGuard™ Medium Ash Natural Gas Engine Oil

PROD. CODE  
7290

ARGuard™ Medium Ash Natural Gas Engine Oil is specialized gas engine oil formulated with advanced additive technology to provide the ultimate protection for four-stroke turbocharged, naturally aspirated, medium and high speed sour or landfill gas engines. It provides a high level of base reserve to control corrosion when high sulfur fuels are used.

## FEATURES & BENEFITS

- Designed to provide extra wear protection when used with fuels containing high levels of contaminants
- Superior oxidation and nitration resistance to ensure minimum viscosity increase
- Promotes maximum valve recession control and head life
- Excellent base number retention promotes extended oil drains

## INDUSTRY & OEM SPECIFICATIONS

- Caterpillar
- Duetz
- GE Jenbacher
- MAN Energy Solutions
- MWM
- Wartsila
- Waukesha

## APPLICATIONS

ARGuard™ Medium Ash Natural Gas Engine Oil is recommended for four-stroke turbocharged, naturally aspirated, medium and high speed engines fueled by sour and landfill gas.

METHOD	DESCRIPTION	TYPICAL
	LBS/GAL	7.395
D4052	API GRAVITY	27.9
D445	VISCOSITY @ 40 °C, cSt	138.6
D445	VISCOSITY @ 100 °C, cSt	14.0
D2270	VISCOSITY INDEX	98
D1500	COLOR	OPAQUE
D5949	POUR POINT, °C	-27
D92	FLASH POINT, °F	450
D2896	TBN	8.4
D874	SULFATED ASH, MASS %	0.83

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

