

ARGuard™ R&O Oils

PROD. CODE
7312, 7367,
7368

ARGuard™ R&O Oils are designed for all modern hydraulic power systems where a rust and oxidation (R&O) oil is recommended. They are formulated to provide protection against rust, corrosion and deposit formation, plus mild wear protection.

FEATURES & BENEFITS

- Excellent oxidation stability and rust corrosion protection
- Good foam resistance
- Select Oxidation inhibitors to minimize sludge and varnish formation

INDUSTRY & OEM SPECIFICATIONS

- ASTM D4304 Type 1
- DIN 51524 Part 1
- Parker Hannifin HF-1
- U.S. Steel 126
- Cincinnati Machine P57 (ISO 150)
- AFNOR E48-600 HL

APPLICATIONS

ARGuard™ R&O Oils are recommended in a wide variety of industrial applications where an R&O oil is required including air compressors, electric motors, non-EP gear reducers, machine tools, sleeve bearings, vacuum pumps and select circulating oil systems

METHOD	DESCRIPTION	TYPICAL		
		ISO 10 (7312)	ISO 150 (7367)	ISO 220 (7368)
	LBS/GAL	7.002	7.40	7.42
D4052	API GRAVITY	36.8	27.8	27.3
D445	VISCOSITY @ 100 °C, cSt	2.65	14.30	18.80
D2270	VISCOSITY INDEX	98.0	95.0	96.0
D1500	COLOR	L 0.5	2.0	3.0
	VISUAL INSPECTION	CLEAR & BRIGHT	CLEAR & BRIGHT	CLEAR & BRIGHT
D92	FLASH POINT, °F	340	485	505

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

