

ARGuard™ Rock Drill Oil

PROD. CODE
7701, 7797,
7768, 7769

ARGuard™ Rock Drill Oil is an adhesive, extreme-pressure (EP) lubricant specially designed for the lubrication of air-powered tools such as rock drills, jackhammers, pavement breakers and drifters. It protects against rust and corrosion and also reduces welding or scoring when under constant shock and high load situations.

FEATURES & BENEFITS

- Contains film strength enhancers and tackifiers to adhere to metal surfaces and minimize wear
- Extends tool life and reduces maintenance costs
- Reduces friction and heat buildup

APPLICATIONS

ARGuard™ Rock Drill Oil is recommended for all rock drills. It is also engineered for mining equipment such as demolition and chipping hammers. ARGuard™ Rock Drill Oil also makes an excellent airline lubricant for pneumatic tools such as impact wrenches, rivet hammers, wood borers, tamers and air hoists.

METHOD	DESCRIPTION	TYPICAL			
		ISO 100 (7797)	ISO 220 (7701)	ISO 320 (7768)	ISO 460 (7769)
CALCULATED	LBS/GAL (g/L)	7.36 (882)	7.43 (890)	7.46 (893)	7.48 (896)
D4052	API GRAVITY	28.8	27.4	26.7	26.2
D445	VISCOSITY @ 40 °C, cSt	105	222	320	460
D445	VISCOSITY @ 100 °C, cSt	12.6	20.4	25.6	32.4
D2270	VISCOSITY INDEX	113	107	104	102
D1500	COLOR	6.5	7.5	7.5	7.5
D5949	POUR POINT, °F (°C)	-27 (-33)	-17 (-27)	-11 (-24)	-6 (-21)
D92	FLASH POINT, °F (°C)	465 (241)	450 (232)	450 (232)	510 (266)

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

