## ARGuard™ Roll Grind Fluid

ARGuard™ Roll Grind Fluid is a premium general purpose emulsifying lubricant that provides excellent cooling and lubricity in a wide range of metalworking operations where heat dissipation is critical. It is formulated with high quality base oil, select emulsifiers, and coupling agents to promote the formation of stable, non-foaming emulsions.

PROD. CODE 7940

## **FEATURES & BENEFITS**

- Extreme-pressure agents assure component protection under severe grinding conditions
- Chlorine free formula
- Protects rolls from rust and corrosion

## **APPLICATIONS**

ARGuard™ Roll Grind Fluid is recommended for a wide range of applications including grinding, stamping, turning, planing, milling, drilling, boring and cutting operations.

METHOD	DESCRIPTION	TYPICAL
	LBS/GAL	7.412
D4052	API GRAVITY	27.7
D445	VISCOSITY @ 40 °C, cSt	28.8
D445	VISCOSITY @ 100 °C, cSt	5.1
D2270	VISCOSITY INDEX	107
D1500	COLOR	L3.5
D5949	POUR POINT, °C	-27
D92	FLASH POINT, °F	370
METHOD 15	VISUAL	CLEAR & BRIGHT

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



