

ARGuard™ Two Stroke Engine Oil

PROD. CODE
7253

ARGuard™ Two Stroke Engine Oil is a premium ashless multi-purpose 2 stroke engine oil. Its modern ashless detergent additive package provides maximum protection for air and water cooled 2 stroke engines. ARGuard™ Two Stroke Engine Oil is pre-diluted with carefully selected solvents for ease of mixing with gasoline and may also be used in direct injection engines.

FEATURES & BENEFITS

- Field proven in air and water cooled engines as well as direct fuel injection (DFI) engines
- Reduces combustion chamber deposits
- High detergency additive package helps keep internal engine componentry clean and prevents ring sticking

INDUSTRY & OEM SPECIFICATIONS

- Johnson/Evinrude®
- Mercury®
- Kawasaki®
- Yamaha®
- Suzuki®

APPLICATIONS

ARGuard™ Two Stroke Engine Oil is recommended for two stroke engines in outboard engines, lawn mowers, motor scooters, snowmobiles, chain saws, portable generators, and snow blowers. Meets or exceeds NMMA TC-W3 and JASO-FB. Always consult your owner's manual for proper fuel/oil ratios.

METHOD	DESCRIPTION	TYPICAL
	LBS/GAL	7.226
D4052	GRAVITY, API	31.9
D445	VISCOSITY @ 40 °C, cSt	36.85
D445	VISCOSITY @ 100 °C, cSt	6.7
D2270	VISCOSITY INDEX	139
VISUAL	COLOR	GREEN
D5949	POUR POINT, °C	-39
D93	FLASH POINT, °F	195
D2983	BROOKFIELD VIS @ -25 °C, cP	3000
D874	SULFATED ASH, MASS %	NIL

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

