

ARGuard™ Waylube

PROD. CODE
7795, 7796,
7799

ARGuard™ Waylube is designed for lubrication and protection of horizontal and vertical machine ways and guides. It is designed with select base oils fortified with extreme pressure and friction modifying additives.

FEATURES & BENEFITS

- Contains a tackifier to help lubricant stay in place
- Superior “metal-wetting” ability
- Non-corrosive to copper and aluminum

INDUSTRY & OEM SPECIFICATIONS

- Cincinnati Machine P-47 (ISO 68)
- Cincinnati Machine P-50 (ISO 220)

APPLICATIONS

ARGuard™ Waylube is recommended horizontal and vertical machine ways and machine tool components such as headstock and translating screws

METHOD	DESCRIPTION	TYPICAL		
		ISO 46 (7799)	ISO 68 (7795)	ISO 220 (7796)
CALCULATED	LBS/GAL (g/L)	7.26 (870)	7.30 (875)	7.41 (887)
D4052	API GRAVITY	30.8	29.9	27.6
D445	VISCOSITY @ 40 °C, cSt	46.0	68.0	220.0
D445	VISCOSITY @ 100 °C, cSt	7.1	9.3	19.8
D2270	VISCOSITY INDEX	116	112	103
D1500	COLOR	L 8.0	L 7.5	8.0
D5949	POUR POINT, °F (°C)	-30 (-33)	5 (-15)	10 (-12)
D92	FLASH POINT, °F (°C)	385 (196)	410 (210)	460 (236)
	VISUAL APPEARANCE	TACKY/STRINGY	TACKY/STRINGY	TACKY/STRINGY
	CINCINNATI MACHINE	“STICK-SLIP” TEST	P-47	P-50

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

