

Kendex[®] 0842

PROD. CODE
4313

Also known as a cylinder stock, the Kendex[®] 0842 is most often utilized in steam cylinder oils as an asphalt modifier or in metalworking applications

FEATURES & BENEFITS

- High viscosity
- Good film strength
- Good lubricity
- Good viscosity builder

APPLICATIONS

Steam cylinder oil, asphalt modifier, metalworking applications

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.59
D1298A	GRAVITY, API	21.1	24.5	24.0
D445	VISCOSITY @ 40°C, cSt			795
D445	VISCOSITY @ 65°C, cSt			170
D445	VISCOSITY @ 100°C, cSt	42	55	46
D2270	VISCOSITY INDEX			101
D92	FLASH POINT, °F (°C)	575 (302)		615 (324)
D5949	POUR POINT, °C (°F)		24 (75.2)	
D524	CARBON RESIDUE, (RAMS)			2.3
D611	ANILINE POINT, °C			128.5

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

