

Kensol[®] 17

PROD. CODE
4107

Kensol[®] 17 is a hydrotreated naphtha solvent most known for its diluency properties, but also offers a low odor, aromatic and sulfur content.

FEATURES & BENEFITS

- Excellent viscosity reducer (cutback) in asphalt applications
- Excellent low temperature characteristics
- Non-corrosive

APPLICATIONS

- Asphalt cutbacks
- Cleaning agent

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
D4052	API GRAVITY	57	60	58
	LBS/GAL			6.23
D56	FLASH POINT, TCC, °F (°C)			25 (-4)
D5949	POUR POINT, °C (°F)			< -57 (< -71)
D86	DISTILLATION, °F			
	IBP	170		185
	5%			212
	50%			256
	95%			339
	EBP		400	363
D7039	SULFUR, ppm			< 2
D4952	DOCTOR TEST			NEGATIVE/SWEET
D130	COPPER STRIP CORROSION, 3HRS @ 122°F			1A
D1133	KAURI BUTANOL VALUE			34.6
D611	ANILINE POINT, °C			60.2
D1319	FIA ANALYSIS, VOL %			
	AROMATICS			10.3
	SATURATES			88.7
D6045/D156	COLOR, SAYBOLT			+30
OLFACTORY	ODOR			MILD PETROLEUM SOLVENT
	VISUAL			CLEAR & BRIGHT

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

 **AMERICAN
REFINING
GROUP, INC.**
Refine everything.™