

ARGuard™ Wireline

PROD. CODE
7747, 7748,
7749

ARGuard™ Wireline is a high-quality, tacky, viscous lubricant specifically formulated for lubrication and sealing of braided wirelines and cables used in oil and gas wells. ARGuard™ Wireline is applied in once-through operation. It is designed to maintain a seal around the moving wireline in high pressure environments and safeguard against corrosive (H₂S) gas. ARGuard™ Wireline's enhanced low temperature fluidity prevents wireline seizure and breakage in cold weather.

FEATURES & BENEFITS

- Excellent sealing capabilities
- Superior corrosion protection
- Tacky texture prevents sling off, splatter and drip

APPLICATIONS

ARGuard™ Wireline is recommended as a lubricant/sealant for braided wirelines, cables and slicklines used in down-hole operations including oil and gas wells, cased-hole logging, pipe recovery and reservoir analysis

**Note: This product is not designed for and should not be used in wire rope applications*

METHOD	DESCRIPTION	TYPICAL		
		ISO 680 (7747)	ISO 1500 (7748)	ISO 2500 (7749)
CALCULATED	DENSITY, LBS/GAL	7.239	7.237	7.236
D445	VISCOSITY, cSt @ 40°C	680	1500	2500
D445	VISCOSITY, cSt @ 100°C	64.5	123.2	166.1
D5949	POUR POINT, °F (°C)	-0.5 (-18)	-0.5 (-18)	-0.5 (-18)
D92	FLASH POINT, °F (°C)	390 (199)	405 (207)	435 (224)

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

