

# Kendex<sup>®</sup> 0846

PROD. CODE  
4317

This waxy specialty product is used as an intermediate in a variety of product applications including microcrystalline waxes, petroleum jellies, laminating wax and cosmetics.

## FEATURES & BENEFITS

- Good cohesive properties

## APPLICATIONS

Precursor to microcrystalline waxes, petroleum jellies, laminating wax, cosmetics and cable filler component

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.43
D1298	GRAVITY, API			26.0
D445	VISCOSITY @ 40°C, cSt			290
D445	VISCOSITY @ 65.6°C, cSt			99
D445	VISCOSITY @ 100°C, cSt	26.0	30.0	28.0
D2270	VISCOSITY INDEX			128
D92	FLASH POINT, °F (°C)	550 (288)		570 (299)
D97	POUR POINT, °C			27
D1500	COLOR, ASTM			OPAQUE
D2622	SULFUR, wt%			0.12
D2007	SATURATES, wt%			68

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

