

# Kendex<sup>®</sup> 0840

PROD. CODE  
4312

Kendex<sup>®</sup> 0840 is designed to meet the properties of traditional steam cylinder oils but with lower pour point for improved low temperature fluidity. This is a heavy viscosity oil with excellent VI.

## FEATURES & BENEFITS

- High viscosity
- High VI
- Strong film forming attributes
- Pourable at room temperature
- Adheres to metal without flaking off during lubricating process

## APPLICATIONS

Steam cylinders for lubricating engines, open gear compounds

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.53
D1298	API GRAVITY	23.5	25.0	24.3
D445	VISCOSITY @ 100°C, cSt	40	50	45
D445	VISCOSITY @ 40°C, cSt (Extrapolated)			795
D445	VISCOSITY @ 65°C, cSt			170
D2270	VISCOSITY INDEX	95		99
D97	POUR POINT, °C		6	3
D92	FLASH POINT, °F (°C)	575 (301)		595 (313)
D524	CARBON RESIDUE (RAMS)			2.3

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

