

# Kendex<sup>®</sup> 0850

PROD. CODE  
4570

Kendex<sup>®</sup> 0850 is used as a component in formulating quench oils.

## FEATURES & BENEFITS

- Increases cooling rate in quench oils
- Thermally stable
- High flash point

## APPLICATIONS

Metalworking, quenching oil

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.57
D1298	API GRAVITY			24.5
D2161	VISCOSITY @ 100°C, cSt	20	23	21.6
D445	VISCOSITY @ 40°C, cSt			228
D2270	VISCOSITY INDEX			113
D4530	CARBON RESIDUE (MICRO METHOD)			5.75
D92	FLASH POINT, °F	350		370

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

