

# Kendex<sup>®</sup> 0888

PROD. CODE  
4608

Kendex<sup>®</sup> 0888 is used as a component in formulating quench oils.

## FEATURES & BENEFITS

- Increases cooling rate in quench oils
- Thermally stable
- Low pour point - can be handled without heating

## APPLICATIONS

Metalworking, quenching oil

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.509
D1298	API GRAVITY	23.6	25.4	24.2
D445	VISCOSITY @ 100°C, cSt	31.5	33.8	32.2
D2161	VISCOSITY @ 100°F, SUS			1949
D2161	VISCOSITY @ 210°F, SUS			163.3
D445	VISCOSITY @ 40°C, cSt			400
D2270	VISCOSITY INDEX			130
D97	POUR POINT, °C			3
D92	FLASH POINT, COC, °F	280		310

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

