

# Kendex<sup>®</sup> HN97

PROD. CODE  
4525

Kendex<sup>®</sup> HN97 is used for directional boring applications where filling of the space between the carrier pipe and conduit requires sealing. Kendex<sup>®</sup> HN97 can also be used as a moisture barrier for applications requiring protection from moisture in areas such as concrete, steel and underground applications.

## FEATURES & BENEFITS

- Good cohesive properties
- Excellent moisture repellency
- Good adherence
- Resilient to environmental conditions

## APPLICATIONS

Fill material for directional pipe borings, underground sealants for concrete and construction products

METHOD	DESCRIPTION	TYPICAL
D1298B	API GRAVITY	30.7
D92	FLASH POINT, °F	555
D445	VISCOSITY @ 100°C, cSt	14.21
D127	MELT POINT, °F	140.5
D721	OIL CONTENT, wt. %	17.24
D1500	COLOR	D8.0

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

