

ARGold Legacy™

PROD. CODE
4318

This bright stock 150 SUS @ 210°F is used as a viscosity builder and provides excellent film strength in boundary lubrication regimes including automotive and industrial gear oils, and other industrial applications.

FEATURES & BENEFITS

- Low sulfur
- Excellent film strength
- Good wetability
- Excellent solvency
- Good VI

APPLICATIONS

Grease, additives, metalworking fluids, automotive & industrial gear oils, and other industrial applications

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.49
D4052	API GRAVITY			26.2
D445	VISCOSITY @ 40°C, cSt			485
D445	VISCOSITY @ 100°C, cSt	30.0	33.7	32.0
D2161	VISCOSITY @ 100°F, SUS			2,600
D2161	VISCOSITY @ 210°F, SUS			155
D2270	VISCOSITY INDEX	95.0		97.0
D92	FLASH POINT, °F (°C)	550 (288)		560 (293)
D97	POUR POINT, °C (°F)		-6 (21.2)	-12 (10.4)
D1500	COLOR, ASTM			7.5
D189	CONRADSON CARBON RESIDUE			0.85
D611	ANILINE POINT, °F (°C)			260 (127)
D664	NEUTRALIZATION NUMBER			0.05
D3238	NDM AROMATIC CARBON, %			8
	NAPHTHENIC CARBON, %			24
	PARAFFINIC CARBON, %			68

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

