

This heavy neutral extract is used in asphalt modification/rejuvenation and rubber compounding. Kendex HNE is produced through solvent extraction of Group I Base Oils.

FEATURES & BENEFITS

- High aromatic content
- Enhances rubber formulations
- Rejuvenates aged asphalt

APPLICATIONS

Rejuvenator/modifier in paving asphalts, DAE in rubber process oils

METHOD	DESCRIPTION	MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			8.31
D4052	API GRAVITY			10.5
D2501	VISCOSITY GRAVITY CONSTANT			0.932
D92	FLASH POINT, COC, °C (°F)	260 (500)		271 (520)
D445	VISCOSITY @ 40°C, cSt			7,100
D445	VISCOSITY @ 100°C, cSt	50		82
D2161	VISCOSITY @ 210°F, SUS			404
D5949	POUR POINT, °C (°F)			39 (102)
D2007	AROMATICS, % wt.			51.2
D4530	CARBON RESIDUE, MICRO METHOD wt %			6.1

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

