

This heavy neutral extract oil is used for asphalt and rubber processing applications. It is sometimes referred to as a heavy neutral extract oil.

## FEATURES & BENEFITS

- High aromatic content
- Enhances tire rubber formulations
- Rejuvenates aged asphalt

## APPLICATIONS

Rejuvenator/modifier in paving asphalts, DAE in rubber process oils

METHOD	DESCRIPTION	MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			8.43
D1298A	API GRAVITY			7.66
D92	FLASH POINT, COC, °F	500		530
D445	VISCOSITY @ 100°C, cSt	50		75
D445	VISCOSITY @ 40°C, cSt			16,100
D5949	POUR POINT, °C			39
D2007	AROMATICS, % wt.			70
D2501	VISCOSITY GRAVITY CONSTANT (PETROLEUM OILS)			0.957

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

