

ARGuard™ Low Ash Natural Gas Engine Oil

PROD. CODE
7249, 7256

ARGuard™ Low Ash Natural Gas Engine Oils are premium performance lubricants formulated with advanced additive technology and Group II base oils to provide the ultimate protection for four-stroke turbocharged, naturally aspirated, medium and high speed natural or landfill gas engines. The low ash formula provides exceptional anti-wear protection to valve-train components while ensuring catalytic converter compatibility and longevity.

FEATURES & BENEFITS

- Promotes low maintenance cost and long engine life
- Low ash formula minimizes valve recession and combustion chamber deposits
- Prevents ring sticking and helps maintain varnish free piston skirts
- Excellent base number retention promotes extended oil drains

INDUSTRY & OEM SPECIFICATIONS

- Caterpillar
- Duetz
- GE Jenbacher
- MAN Energy Solutions
- MWM
- Wartsila
- Waukesha

APPLICATIONS

ARGuard™ Low Ash Natural Gas Engine Oil is recommended for four-stroke turbocharged, naturally aspirated, medium and high speed engines fueled by sour and landfill gas.

METHOD	DESCRIPTION	TYPICAL	
		40 (7249)	15W-40 (7256)
	LBS/GAL	7.35	7.25
D4052	API GRAVITY	28.8	31.2
D445	VISCOSITY @ 40 °C, cSt	129.9	113.7
D445	VISCOSITY @ 100 °C, cSt	13.7	14.4
D2270	VISCOSITY INDEX	101	129
D1500	COLOR	3.5	L3.5
D5949	POUR POINT, °C	-21	-33
D92	FLASH POINT, °F	450	490
D2896	TBN	5.1	4.9
D874	SULFATED ASH, wt. %	0.45	0.46

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

