

This high viscosity aromatic extract oil is used in asphalt modification/rejuvenation and rubber compounding applications. It is sometimes referred to as a bright stock extract oil.

## FEATURES & BENEFITS

- High aromatic content
- Enhances rubber formulations
- Rejuvenates aged asphalt

## APPLICATIONS

Rejuvenator/modifier in paving asphalts, DAE in rubber process oils, used as a plasticizer in adhesives and coatings

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			8.35
D4052	API GRAVITY			9.8
D2501	VISCOSITY GRAVITY CONSTANT			0.970
D92	FLASH POINT, COC, °C (°F)	260 (500)		299 (570)
D445	VISCOSITY @ 100°C, cSt	100.0		230.0
D2161	VISCOSITY @ 210°F, SUS			1,144
D2270	VISCOSITY INDEX			-16
D5949	POUR POINT, °C (°F)			42 (108)
D1500	COLOR			D8.0
D2007	SATURATES, % wt.			18.1
D2007	AROMATICS, % wt.			61.3
D4530	CARBON RESIDUE, MICRO METHOD wt %			10.7

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

