

Kendex® 0898

PROD. CODE
4618

An intermediate resin that is usually reserved for the metalworking industry as a viscosity builder. This resin is also black and highly viscous. A specialty blend of Penn Resin, Kendex® 0898 can be used as a quench oil additive.

FEATURES & BENEFITS

- Control cooling characteristics in quench oils

APPLICATIONS

Quench oil additive

		SPECIFICATIONS		
METHOD	DESCRIPTION	MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.77
D1298	API GRAVITY	16.1	21.9	20.4
D445	VISCOSITY @ 100°C, cSt	105.6	123.6	116.7
D445	VISCOSITY @ 40°C, cSt			4325.0
D2270	VISCOSITY INDEX			92.0
D5949	POUR POINT, °C			12
D92	FLASH POINT, COC, °F (°C)	600 (316)		630 (332)
D1500	COLOR, ASTM			OPAQUE
D4530	CARBON RESIDUE, MICRO METHOD wt %			6.0

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

