

Kendex[®] 200H

PROD. CODE
4300

This hydrotreated 200 SUS solvent neutral base oil is utilized in process oils including rubber and plasticizer applications.

FEATURES & BENEFITS

- Good solubility
- Improved color
- Improved oxidative stability
- High viscosity index
- Excellent solvency characteristics

APPLICATIONS

Process oils, hydraulic oils, metalworking, rubber and plasticizer applications

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.25
D4052	API GRAVITY			31.3
D445	VISCOSITY @ 40°C, cSt	39.0	42.0	40.7
D445	VISCOSITY @ 100°C, cSt			6.4
D2270	VISCOSITY INDEX			106
D92	FLASH POINT, °F (°C)	380 (193)		440 (227)
D5949	POUR POINT, °C (°F)		-9 (16)	-12 (10)
D1500	COLOR			L3.0
D7039	SULFUR, mg/kg			270

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

