

Kendex[®] 250H

PROD. CODE
4301

This hydrotreated 250 SUS solvent neutral base oil is well suited as a blending stock for an ISO VG 46 hydraulic fluid.

FEATURES & BENEFITS

- Good solubility
- Improved color
- Improved oxidative stability
- High viscosity index
- Excellent solvency characteristics

APPLICATIONS

Hydraulic oils, diluent and carrier fluids, rubber process oils, plasticizers

| METHOD | DESCRIPTION | SPECIFICATIONS | | |
|--------|------------------------|----------------|---------|-----------|
| | | MINIMUM | MAXIMUM | TYPICAL |
| | LB/GAL | | | 7.26 |
| D4052 | API GRAVITY | | | 31.0 |
| D445 | VISCOSITY @ 40°C, cSt | 42.0 | 55.0 | 46.8 |
| D445 | VISCOSITY @ 100°C, cSt | | | 7.0 |
| D2270 | VISCOSITY INDEX | | | 106 |
| D92 | FLASH POINT, °F (°C) | 380 (193) | | 430 (221) |
| D5949 | POUR POINT, °C (°F) | | -9 (16) | -12 (10) |
| D1500 | COLOR | | | L2.5 |
| D7029 | SULFUR, mg/kg | | | 280 |

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

