

Kendex[®] 500H

PROD. CODE
4310

This hydrotreated 500 SUS solvent neutral base oil is used as a viscosity builder in industrial gear and marine oils.

FEATURES & BENEFITS

- Good solubility
- Improved color
- Improved oxidative stability
- High viscosity index
- Excellent solvency characteristics

APPLICATIONS

Industrial gear oils, marine oils, diluent and carrier fluids, rubber process oils, plasticizers

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.32
D4052	API GRAVITY			29.7
D445	VISCOSITY @ 40°C, cSt	96.0	106.0	98.2
D445	VISCOSITY @ 100°C, cSt			11.4
D2270	VISCOSITY INDEX			103
D92	FLASH POINT, °F (°C)	435 (224)		450 (232)
D5949	POUR POINT, °C (°F)		-6 (21)	-12 (10)
D1500	COLOR, ASTM			4.5
D7029	SULFUR, mg/kg			300

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

