

ARGuard™ Saw Guide Oil 22

PROD. CODE
7798

ARGuard™ Saw Guide Oil 22 is a high quality, saw blade/saw guide lubricant specifically formulated for sawmill lumber production.

FEATURES & BENEFITS

- Reduces heat build-up/blade “bluing”
- Proprietary technology to help prevent pitch build up
- Affords excellent lubricity and solvency
- Oil stays on blade/prevents oil “sling-off”
- Imparts outstanding friction reduction
- Superior rust and corrosion protection
- Evaluated and field proven/designed and ideally suited for hardwood lumber production

APPLICATIONS

ARGuard™ Saw Guide Oil 22 was specifically designed and formulated with Pennsylvania Grade base stocks and carefully selected additives to address the lubricant demands of saw blades and saw guides. ARGuard™ Saw Guide Oil 22 provides excellent lubricity in addition to solvency, providing dual performance attributes resulting in less saw and guide maintenance and lower operating expenses.

METHOD	DESCRIPTION	TYPICAL
	LBS/GAL	7.226
D4052	GRAVITY, API	31.8
D445	VISCOSITY @ 40 °C, cSt	21.18
D445	VISCOSITY @ 100 °C, cSt	4.68
D2270	VISCOSITY INDEX	144
D1500	COLOR	2
D5949	POUR POINT, °C	-33
D92	FLASH POINT, °F	392
D6481	SULFUR, MASS %	0.046
D6481	PHOSPHORUS, MASS %	0.028

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

