

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 1 of 12

Revision date: 01.20.2026

Kensol® 17

SECTION 1: Identification

Product Identifier

Product Name: Kensol® 17

Product code: 4107

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Asphalt Naphtha Solvent

Uses Advised Against: Not determined or not applicable.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

American Refining Group
77 North Kendall Avenue
Bradford, Pennsylvania 16701
814-368-1297
msds@amref.com
amref.com

Emergency Telephone Number:

United States

CHEMTREC
1-800-424-9300 (24 Hours)

United States

American Refining Group
814-368-1297 (24 Hours)

SECTION 2: Hazard(s) Identification

GHS Classification:

Flammable liquids, category 2

Skin irritation, category 2

Germ cell mutagenicity, category 1B

Carcinogenicity, category 1B

Reproductive toxicity, category 2

Specific target organ toxicity - single exposure, category 3, narcotic effects

Aspiration hazard, category 1

Label elements

Hazard Pictograms:



Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 2 of 12

Revision date: 01.20.2026

Kensol® 17

Signal Word: Danger

Hazard statements:

- H225 Highly flammable liquid and vapor
- H315 Causes skin irritation
- H340 May cause genetic defects.
- H350 May cause cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H304 May be fatal if swallowed and enters airways.

Precautionary Statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical, ventilating, and lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P264 Wash skin thoroughly after handling.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P370+P378 In case of fire: Use agents recommended in Section 5 to extinguish.
- P302+P352 IF ON SKIN: Wash with plenty of water and soap.
- P321 Specific treatment (see Sections 4-8 of this SDS and any supplemental information on the product label).
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362 Take off contaminated clothing and wash it before reuse.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P331 Do NOT induce vomiting.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P403+P235 Store in a well-ventilated place. Keep cool and keep container tightly closed.
- P405 Store locked up
- P501 Dispose of contents and container in accordance with local, regional, national, and international regulations.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 64741-42-0	Naphtha (petroleum), full-range straight-run	100

Additional Information: None

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 3 of 12

Revision date: 01.20.2026

Kensol® 17

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Product is highly flammable. Exposure to sources of ignition may cause physical injury.

Skin contact may result in redness, pain, burning and inflammation.

Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness.

May be fatal if swallowed and enters airways. Aspiration may cause pulmonary edema and pneumonitis. Symptoms may include shortness of breath, dry cough and irritation of the nose, eyes, lips, mouth and throat.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Exposure may cause genetic defects. Effects are dependent on exposure (dose, concentration, contact time).

Exposure may cause cancer. Effects are dependent on exposure (dose, concentration, contact time).

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

Symptoms of pulmonary edema may be delayed.

Immediate Medical Attention and Special Treatment

Specific Treatment:

Skin/eye burns require immediate treatment.

Overexposure via inhalation requires urgent medical treatment.

Notes for the Doctor:

Treat symptomatically.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 4 of 12

Revision date: 01.20.2026

Kensol® 17

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Highly flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 5 of 12

Revision date: 01.20.2026

Kensol® 17

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	Naphtha (petroleum), full-range straight-run	64741-42-0	8-Hour TWA-PEL: 2000 mg/m ³ ([500 ppm] Petroleum Distillates (Naphtha, Rubber Solvent))
	Naphtha (petroleum), full-range straight-run	64741-42-0	8-Hour TWA-PEL: 5 mg/m ³ (Mineral oil)
NIOSH	Naphtha (petroleum), full-range straight-run	64741-42-0	REL-TWA: 350 mg/m ³ ([up to 10 hr] Petroleum Distillates (Naphtha, Rubber Solvent))
	Naphtha (petroleum), full-range straight-run	64741-42-0	Ceiling Limit: 1800 mg/m ³ (Petroleum Distillates (Naphtha, Rubber Solvent))
	Naphtha (petroleum), full-range straight-run	64741-42-0	REL-TWA: 400 mg/m ³ ([100 ppm] Naphtha [up to 10 hr])
	Naphtha (petroleum), full-range straight-run	64741-42-0	IDLH: 1000 ppm (Naphtha)
	Naphtha (petroleum), full-range straight-run	64741-42-0	REL-TWA: 5 mg/m ³ (Mineral oil [up to 10 hr])
	Naphtha (petroleum), full-range straight-run	64741-42-0	15-Minute STEL: 10 mg/m ³ (Mineral oil)
	Naphtha (petroleum), full-range straight-run	64741-42-0	IDLH: 2500 mg/m ³ (Mineral oil)
United States(California)	Naphtha (petroleum), full-range straight-run	64741-42-0	8-Hour TWA-PEL: 1600 mg/m ³ ([400 ppm] Petroleum Distillates (Naphtha, Rubber Solvent))
	Naphtha (petroleum), full-range straight-run	64741-42-0	8-Hour TWA-PEL: 5 mg/m ³ (Mineral oil, particulate)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 6 of 12

Revision date: 01.20.2026

Kensol® 17

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Naphtha (petroleum), full-range straight-run	64741-42-0	8-Hour TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, highly & severely refined, inhalable particulate matter)

Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Colorless
Odor	Hydrocarbon Solvent
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	179°F / 179°F - 400°F
Flash point (closed cup)	29°F
Evaporation rate	Not determined or not available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 7 of 12

Revision date: 01.20.2026

Kensol® 17

Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	6.25 vol %
Lower flammability/explosive limit	0.75 vol %
Vapor pressure	50 - 100
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	6.217 lbs/gal
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	473°F
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Naphtha (petroleum), full-range straight-run	oral	LD50 Rat: > 5000 mg/kg
	dermal	LD50 rabbit: > 2000 mg/kg
	inhalation	LC50 rat: > 8530 mg/m ³ (4hr [vapour])

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 8 of 12

Revision date: 01.20.2026

Kensol® 17

Product Data:

No data available.

Substance Data:

Name	Result
Naphtha (petroleum), full-range straight-run	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Carcinogenicity

Assessment:

May cause cancer.

Product Data: No data available.

Substance Data:

Name	Species	Result
Naphtha (petroleum), full-range straight-run		May cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Naphtha (petroleum), full-range straight-run	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Naphtha (petroleum), full-range straight-run	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment:

May cause genetic defects.

Product Data:

No data available.

Substance Data:

Name	Result
Naphtha (petroleum), full-range straight-run	May cause genetic defects.

Reproductive Toxicity

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 9 of 12

Revision date: 01.20.2026

Kensol® 17

Assessment:

Suspected of damaging fertility or the unborn child.

Product Data:

No data available.

Substance Data:

Name	Result
Naphtha (petroleum), full-range straight-run	Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure)

Assessment:

May cause drowsiness or dizziness.

Product Data:

No data available.

Substance Data:

Name	Result
Naphtha (petroleum), full-range straight-run	May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Aspiration toxicity

Assessment:

May be fatal if swallowed and enters airways.

Product Data:

No data available.

Substance Data:

Name	Result
Naphtha (petroleum), full-range straight-run	May be fatal if swallowed and enters airways.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 10 of 12

Revision date: 01.20.2026

Kensol® 17

Name	Result
Naphtha (petroleum), full-range straight-run	Aquatic Invertebrates LC50 Mysidopsis bahia: 2 mg/L (48 hr)
	Aquatic Plants EC50 Pseudokirchneriella subcapitata: 4700 mg/L (72 hr)

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Naphtha (petroleum), full-range straight-run	Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Naphtha (petroleum), full-range straight-run	The substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Naphtha (petroleum), full-range straight-run	The substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Naphtha (petroleum), full-range straight-run	The substance is not PBT.
--	---------------------------

vPvB assessment:

Naphtha (petroleum), full-range straight-run	The substance is not vPvB.
--	----------------------------

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 11 of 12

Revision date: 01.20.2026

Kensol® 17

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	1268
UN Proper Shipping Name	Petroleum Distillates Naphtha
UN Transport Hazard Class(es)	3 
Packing Group	II
Environmental Hazards	None
Special Precautions for User	None
Additional Information	Bulk containers must be labeled on two opposing sides. Non-bulk containers must be labeled on one side or end.

International Maritime Dangerous Goods (IMDG)

UN Number	1268
UN Proper Shipping Name	Petroleum Distillates Naphtha
UN Transport Hazard Class(es)	3 
Packing Group	II
Environmental Hazards	None
Special Precautions for User	None
Additional Information	Bulk containers must be labeled on two opposing sides. Non-bulk containers must be labeled on one side or end.

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	1268
UN Proper Shipping Name	Petroleum Distillates Naphtha
UN Transport Hazard Class(es)	3 
Packing Group	II
Environmental Hazards	None
Special Precautions for User	None
Limited Quantity	Maximum Net Quantity: 60L

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 01.12.2021

Page 12 of 12

Revision date: 01.20.2026

Kensol® 17

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals: None of the ingredients are listed.

CERCLA:

64741-42-0	Naphtha (petroleum), full-range straight-run	Listed	100 lbs
------------	--	--------	---------

RCRA:

64741-42-0	Naphtha (petroleum), full-range straight-run	Listed	D001
------------	--	--------	------

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know: None of the ingredients are listed.

New Jersey Right to Know: None of the ingredients are listed.

New York Right to Know: None of the ingredients are listed.

Pennsylvania Right to Know: None of the ingredients are listed.

California Proposition 65:

⚠ WARNING: This product can expose you to chemicals including Toluene, Benzene and Ethylbenzene which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

NFPA: 1-3-0

HMIS: 1-3-0

Initial Preparation Date: 01.12.2021

Revision date: 01.20.2026

End of Safety Data Sheet