

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 1 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

SECTION 1: Identification

Product Identifier

Product Name: ARGuard 2-Stroke Engine Oil 2T

Product code: 7253

Recommended Use of the Chemical and Restrictions on Use:

Recommended Uses: 2 Stroke Engine Oil

Restrictions on Use: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

American Refining Group
77 North Kendall Avenue
Bradford, Pennsylvania 16701
814-368-1297
msds@amref.com
amref.com

Emergency Telephone Number:

United States

CHEMTREC
1-800-424-9300 (24 Hours)

United States

American Refining Group
814-368-1297 (24 Hours)

SECTION 2: Hazard Identification

Classification of the chemical in accordance with paragraph (d) of § 1910.1200:

Flammable liquids, category 4

Skin irritation, category 2

Label elements

Hazard Symbol(s):



Signal Word: Warning

Hazard statement(s):

H227 Combustible liquid

H315 Causes skin irritation

Precautionary Statement(s):

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

P264 Wash skin thoroughly after handling.

P370+P378 In case of fire: Use dry chemical, carbon dioxide, water spray, or foam for extinction.

P302+P352 If on skin: Wash with plenty of water and soap.

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 2 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

P321 Specific treatment (see Sections 4-8 of this SDS and any supplemental information on the product label).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P403 Store in a well-ventilated place.

P501 Dispose of contents and container in accordance with federal, state and local regulations.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	20-25
CAS Number: 64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic	20-25
CAS Number: 64742-47-8	Distillates (petroleum), hydrotreated light	20-25
CAS Number: 64742-01-4	Residual oils (petroleum), solvent-refined	15-20

Additional information: No additional information

SECTION 4: First Aid Measures

Description of Necessary Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention

After Ingestion:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Product is combustible. Exposure to sources of ignition may cause physical injury
Skin contact may result in redness, pain, burning and inflammation

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time)

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 3 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Immediate Medical Attention:

Skin/eye burns require immediate treatment

Special Treatment:

No additional information.

Notes for the Doctor:

Treat symptomatically

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Dry chemical, CO₂, water spray or alcohol-resistant foam

Unsuitable Extinguishing Media:

Do not use water jet

Specific Hazards Arising From The Chemical:

Combustible liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation

Thermal decomposition may produce irritating/toxic fumes/gases

Special Protective Equipment and Precautions for Fire-Fighters

Special Protective Equipment:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode

Special precautions

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 4 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13)

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Distillates (petroleum), hydrotreated heavy paraffinic (contains	64742-54-7	8-Hour TWA: 5 mg/m ³ (As Paraffin oils: excluding metal working fluids, highly & severely refined, inhalable particulate matter)
	Residual oils (petroleum), solvent-refined	64742-01-4	8-Hour TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction)
	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA: 200 mg/m ³ (Kerosene and jet-fuels [non-aerosol], as total hydrocarbon vapor)
NIOSH	Distillates (petroleum), hydrotreated heavy paraffinic (contains	64742-54-7	REL-TWA: 5 mg/m ³ (As Paraffin oils [up to 10 hr])
	Distillates (petroleum), hydrotreated heavy paraffinic (contains	64742-54-7	IDLH: 2500 mg/m ³ (As Paraffin oils)
	Distillates (petroleum), hydrotreated heavy paraffinic (contains	64742-54-7	15-Minute STEL: 10 mg/m ³ (As Paraffin oils)
	Distillates (petroleum), hydrotreated light	64742-47-8	REL-TWA: 350 mg/m ³ (up to 10 hr [petroleum distillates, naphtha])

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 5 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Distillates (petroleum), hydrotreated light	64742-47-8	Ceiling Limit: 1800 mg/m ³ ([15 min] petroleum distillates, naphtha)
	Distillates (petroleum), hydrotreated light	64742-47-8	REL-TWA: 100 mg/m ³ (up to 10 hr [kerosene])
United States(California)	Distillates (petroleum), hydrotreated heavy paraffinic (contains	64742-54-7	8-Hour TWA-PEL: 5 mg/m ³ (As Paraffin oils, particulate)
	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA-PEL: 1600 mg/m ³ (400 ppm [aliphatic hydrocarbons])
OSHA	Distillates (petroleum), hydrotreated heavy paraffinic (contains	64742-54-7	8-Hour TWA-PEL: 5 mg/m ³ (As Paraffin oils)
	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA-PEL: 2000 mg/m ³ (500 ppm [aliphatic hydrocarbons])

Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Individual Protection Measures, Such as Personal Protective Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Physical state	Liquid
Color	Green

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 6 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

Odor (includes odor threshold)	Mild
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flammability	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Flash point	195°F
Auto-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
pH	Not determined or not available.
Kinematic viscosity	36.8 cSt (40°C mm ² /s)
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Vapor pressure (includes evaporation rate)	Not determined or not available.
Density and/or relative density	7.2 lbs/gal
Relative vapor density	Not determined or not available.
Particle characteristics	Not determined or not available.

Other Information

No additional information.

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions, including those associated with foreseeable emergencies:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rabbit: > 5000 mg/kg
	inhalation	LC50 Rat: >5.3 mg/L (4 hr [aerosol])

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 7 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

Name	Route	Result
Distillates (petroleum), solvent-refined heavy paraffinic	oral	LD50 Rat: >5000 mg/kg
	inhalation	LC50 Rat: 2.18 mg/L (4hr [aerosol])
	dermal	LD50 Rabbit: >5000 mg/kg
Residual oils (petroleum), solvent-refined	oral	LD50 Rat: >5000 mg/kg
	inhalation	LC50 Rat: >5.3 mg/L (4 hr [Aerosol])
	dermal	LD50 Rabbit: >5000 mg/kg
Distillates (petroleum), hydrotreated light	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
	inhalation	LC50 Rat: >5.2 mg/L (4 hr [vapor])

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated light	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Species	Result
Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)		The classification as a carcinogen does not apply because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

International Agency for Research on Cancer (IARC):

Name	Classification
Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	Not Applicable
Distillates (petroleum), solvent-refined heavy paraffinic	Not Applicable

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 8 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

Name	Classification
Residual oils (petroleum), solvent-refined	Not Applicable
Distillates (petroleum), hydrotreated light	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	Not Applicable
Distillates (petroleum), solvent-refined heavy paraffinic	Not Applicable
Residual oils (petroleum), solvent-refined	Not Applicable
Distillates (petroleum), hydrotreated light	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Interactive effects:

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 9 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

No additional information.

Other Information:

No additional information.

SECTION 12: Ecological Information

Ecotoxicity

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	Fish LC50 Pimephales promelas: > 100 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: > 10,000 mg/L (48 hr [mobility, Read-across substance data])
Distillates (petroleum), hydrotreated light	Fish LC50 Oncorhynchus mykiss: 2 - 5 mg/L (96 hr [LL50 - mortality])
	Aquatic Invertebrates EC50 Daphnia magna: 3 - 10 mg/L (48 hr [EL50 - mobility])
	Aquatic Plants EC50 Raphidocelis subcapitata: 8.3 mg/L (72 hr [EL50 - growth rate])

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	Fish NOEC Oncorhynchus mykiss: >= 1000 mg/L (14 d [NOELR- mortality, QSAR data])
	Aquatic Invertebrates NOEC Daphnia magna: 10 mg/L (21 d [NOEL- reproduction, Read-across substance data])
Distillates (petroleum), hydrotreated light	Fish NOEC Oncorhynchus mykiss: 0.098 mg/L (28 d [NOE- mortality, QSAR substance data])
	Aquatic Invertebrates NOEC Daphnia magna: 0.89 mg/L (21 d [EL50 - reproduction])

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	Standard biodegradability studies are not applicable to petroleum UVCB substances.
Distillates (petroleum), solvent-refined heavy paraffinic	The substance is inherently biodegradable. 31% degradation measured by O2 consumption after 28 days.
Residual oils (petroleum), solvent-refined	The substance is inherently biodegradable. 3.41% degradation measured by O2 consumption after 28 days.
Distillates (petroleum), hydrotreated light	Standard biodegradability studies are not applicable to petroleum UVCB substances.

Bioaccumulative Potential

Product Data: No data available.

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 10 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	Standard bioaccumulation studies are not applicable to petroleum UVCB substances.
Distillates (petroleum), solvent-refined heavy paraffinic	The substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
Residual oils (petroleum), solvent-refined	The substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
Distillates (petroleum), hydrotreated light	Standard bioaccumulation studies are not applicable to petroleum UVCB substances.

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	Standard adsorption/desorption studies are not applicable to petroleum UVCB substances.
Distillates (petroleum), solvent-refined heavy paraffinic	The substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
Residual oils (petroleum), solvent-refined	The substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
Distillates (petroleum), hydrotreated light	Standard adsorption/desorption studies are not applicable to petroleum UVCB substances.

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	The substance is not PBT.
Distillates (petroleum), solvent-refined heavy paraffinic	The substance is not PBT.
Residual oils (petroleum), solvent-refined	The substance is not PBT.
Distillates (petroleum), hydrotreated light	Standard PBT studies are not applicable to petroleum UVCB substances.

vPvB assessment:

Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	The substance is not vPvB.
--	----------------------------

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 11 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

Distillates (petroleum), solvent-refined heavy paraffinic	The substance is not vPvB.
Residual oils (petroleum), solvent-refined	The substance is not vPvB.
Distillates (petroleum), hydrotreated light	Standard vBvB studies are not applicable to petroleum UVCB substances.

Other Adverse Effects: No additional information.

SECTION 13: Disposal Considerations

Disposal Methods:

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

Contaminated packaging:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	1268
UN Proper Shipping Name	Petroleum Distillates Light Distillate
UN Transport Hazard Class(es)	Combustible Liquid 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	Bulk container must be labeled on two opposing sides. U.S. DOT Non-Bulk is Not Regulated.
Reportable Quantity	Over 119 gallons.

International Maritime Dangerous Goods (IMDG)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 12 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	Not Applicable
Ship Type	Not Applicable
Pollution Category	Not Applicable

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals: None of the ingredients are listed.

CERCLA:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed	
------------	---	--------	--

RCRA:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed	D001
------------	---	--------	------

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	Listed	
64742-47-8	Distillates (petroleum), hydrotreated light	Listed	

New Jersey Right to Know:

64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	Listed	
64742-47-8	Distillates (petroleum), hydrotreated light	Listed	

New York Right to Know:

64742-47-8	Distillates (petroleum), hydrotreated light	Listed	
------------	---	--------	--

Pennsylvania Right to Know:

64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic (contains <3% DMSO extract)	Listed	
64742-47-8	Distillates (petroleum), hydrotreated light	Listed	

California Proposition 65: None of the ingredients are listed.

Additional information: No additional information.

SECTION 16: Other Information

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

NFPA: 1-2-0

HMIS: 1-2-0

Initial Preparation Date: 09.01.2020

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 09.01.2020

Page 13 of 13

Revision date: 02.16.2026

ARGuard 2-Stroke Engine Oil 2T

Revision date: 02.16.2026

End of Safety Data Sheet