

ARG D-FOAM 110

PROD. CODE
4337

Low viscosity paraffinic oils used as a base or carrier of the defoamer

FEATURES & BENEFITS

- Cost-effective carrier oil
- Reliability of defoaming effect
- Prevent surface defects

APPLICATIONS

Pulp and paper, paints, coatings, adhesives, and wastewater treatment

REGULATORY

- Non-detect DBD/DBF
- FDA 21CFR178.3620(c) compliance
- EU REACH Registered

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
D4052	API GRAVITY			32.8
	LBS/GAL			7.181
	DENSITY, g/mL			0.8603
D445	VISCOSITY @ 40°C, cSt	20.7	23.5	22.1
D445	VISCOSITY @ 100°C, cSt			4.3
D2161	VISCOSITY @ 100°F, SUS			116
D2161	VISCOSITY @ 210°F, SUS			41
D1500	COLOR		1.0	0.8
D5949	POUR POINT, °C			-15
D92	FLASH POINT, °F			385
D6304	KF MOISTURE, ppm		100	
EPA 1613B	DIOXINS & FURANS BY HRGC/HRMS, pg/g			0.0
D664	ACID NUMBER, mg KOH/g			0.01
D4530	CARBON RESIDUE (Micro Method), MASS %			<0.05
D7039	SULFUR, MASS %			0.0242
D611	ANILINE POINT, °C			100.1
D2501	VISCOSITY GRAVITY CONSTANT			0.810
	MOLECULAR WEIGHT, g/mole			371
D1218	REFRACTIVE INDEX @ 20°C			1.4750
D3238	n-d-M CARBON DISTRIBUTION:			
	% C AROMATIC			6
	% C NAPHTHENIC			26
	% C PARAFFINIC			68
D2007	SATURATES, MASS %			83.8
	AROMATICS, MASS %			16.1
	POLARS, MASS %			0.1

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

