

ARGuard™ Multi-Purpose GL-5 Gear Oil

PROD. CODE
7730, 7735

ARGuard™ Multi-Purpose GL-5 Gear Oils are high performance, multi-grade, extreme-pressure, multi-purpose lubricants. These gear oils offer excellent performance in automotive axles, gear sets and differentials. ARGuard™ Multi-Purpose GL-5 Gear Oils are formulated with quality base oils and carefully selected additives which provide excellent anti-wear protection under heavy loads.

FEATURES & BENEFITS

- Maximum protection against scuffing and wear
- Excellent load carrying capacity
- Outstanding rust and corrosion protection

APPLICATIONS

ARGuard™ Multi-Purpose GL-5 Gear Oils can be used in heavy duty and conventional differentials, in heavy duty and light duty trucks as well as passenger cars. Recommended for use in conventional transmissions calling for API GL-5.

METHOD	DESCRIPTION	TYPICAL	
		80W-90 (7730)	85W-140 (7735)
	LBS/GAL	7.396	7.468
D4052	API GRAVITY	28.0	26.5
D445	VISCOSITY @ 40°C, cSt	139	327
D2270	VISCOSITY INDEX	106	99
D1500	COLOR	6.0	<7.5
D5949	POUR POINT, °C	-27	-21
D92	FLASH POINT, °F	435	440

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

