

Kendex[®] 0070

PROD. CODE
4303

This 70 SUS solvent neutral base oil is often used as both a light viscosity lubricant blend stock and a process oil in a variety of applications such as dust suppression, metalworking fluids and defoamers.

FEATURES & BENEFITS

- Low sulfur
- Good solvency

REGULATORY

- Meets 21 CFR 178.3620(c) mineral oil as component of non-food articles intended for use in contact with food (FDA regulations)
- EU REACH Registered

APPLICATIONS

Metalworking, defoamers, automatic transmission fluids, horticultural spray oils, industrial and agricultural dust suppression, light viscosity hydraulic oils, spindle oils

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
D4052	API GRAVITY			34.1
	LBS/GAL			7.13
D445	VISCOSITY @ 40°C, cSt	12.7	13.7	13.3
D445	VISCOSITY @ 100°C, cSt			3.1
D2270	VISCOSITY INDEX			93
D1500	COLOR, ASTM		1.0	0.5
D5949	POUR POINT, °C (°F)			-18 (0)
D92	FLASH POINT, °F (°C)			375 (191)

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

