Kendex® 0851

Kendex® 0851 is used as a component in formulating quench oils.

PROD. CODE
4571

FEATURES & BENEFITS

- Increases cooling rate in quench oils
- Thermally stable
- High flash point

APPLICATIONS

Metalworking, quenching oil

		SPECIFICATIONS		
METHOD	DESCRIPTION	MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.67
D1298	**API GRAVITY**	21.7	23.7	22.4
D2161	**VISCOSITY @ 210°F,** SUS			300
D445	**VISCOSITY @ 100°C,** cSt	62.0	65.0	63.9
D445	**VISCOSITY @ 40°C,** cSt			1480
D2270	**VISCOSITY INDEX**			98
D92	**FLASH POINT,** °F	575		610

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.

amref.com | 814.368.1200

AMERICAN REFINING GROUP, INC.
Refine everything.™

REV 9/23/2026