

# Kendex® 0888

PROD. CODE  
4608

Kendex® 0888 is used as a component in formulating quench oils.

## FEATURES & BENEFITS

- Increases cooling rate in quench oils
- Thermally stable
- Low pour point - can be handled without heating

## APPLICATIONS

Metalworking, quenching oil

## REGULATORY

EU REACh Registered

| METHOD | DESCRIPTION            | SPECIFICATIONS |         |         |
|--------|------------------------|----------------|---------|---------|
|        |                        | MINIMUM        | MAXIMUM | TYPICAL |
|        | LBS/GAL                |                |         | 7.509   |
| D1298  | API GRAVITY            | 23.6           | 25.4    | 24.2    |
| D445   | VISCOSITY @ 100°C, cSt | 31.5           | 33.8    | 32.2    |
| D2161  | VISCOSITY @ 100°F, SUS |                |         | 1949    |
| D2161  | VISCOSITY @ 210°F, SUS |                |         | 163.3   |
| D445   | VISCOSITY @ 40°C, cSt  |                |         | 400     |
| D2270  | VISCOSITY INDEX        |                |         | 130     |
| D97    | POUR POINT, °C         |                |         | 3       |
| D92    | FLASH POINT, COC, °F   | 280            |         | 310     |

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

