

Kendex® 1200

PROD. CODE
4573

Kendex® 1200 is used as a component in formulating quench oils.

FEATURES & BENEFITS

- Increases cooling rate in quench oils
- Thermally stable
- Good thermal convection properties

APPLICATIONS

Metalworking, quenching oil

REGULATORY

EU REACH Registered

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.58
D1298	DENSITY @ 15.6°C	.8940	.9200	.908
D445	VISCOSITY @ 100°C, cSt	22	28	25
D445	VISCOSITY @ 40°C, cSt			286
D2270	VISCOSITY INDEX			112
D1500	COLOR			D8.0 (OPAQUE)
D92	FLASH POINT, °C (°F)	170 (338)		191
D4530	CARBON RESIDUE (MICRO METHOD), MASS %		8.0	6.8

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

