

Kendex[®] 300H

PROD. CODE
4304

This hydrotreated 300 SUS solvent neutral base oil is used in a variety of industrial applications.

FEATURES & BENEFITS

- Good solubility
- Improved color
- Improved oxidative stability
- High viscosity index
- Excellent solvency characteristics

APPLICATIONS

Diluent and carrier fluids, rubber process oils, plasticizers, hydraulic oils

REGULATORY

EU REACH Registered

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LB/GAL			7.28
D4052	API GRAVITY			30.6
D445	VISCOSITY @ 40°C, cSt	58.0	62.0	60.0
D445	VISCOSITY @ 100°C, cSt			8.3
D2270	VISCOSITY INDEX			107
D92	FLASH POINT, °F (°C)	405 (207)		440 (227)
D5949	POUR POINT, °C (°F)		-6 (21)	-9 (16)
D1500	COLOR, ASTM			L3.0
D7029	SULFUR, mg/kg			280

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

