

Kendex[®] 600H

PROD. CODE
4316

This hydrotreated 600 SUS solvent neutral base oil is used as a viscosity builder in industrial gear and marine oils.

FEATURES & BENEFITS

- Good solubility
- Improved color
- Improved oxidative stability
- High viscosity index
- High flash point
- Excellent solvency characteristics

APPLICATIONS

Industrial gear oils, marine oils, lubricant blending component, process oil, manufacturing intermediate

REGULATORY

EU REACh Registered

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.33
D4052	API GRAVITY			29.5
D445	VISCOSITY @ 40°C, cSt	108.0	118.0	109.8
D445	VISCOSITY @ 100°C, cSt	12.0	12.7	12.2
D2270	VISCOSITY INDEX			102
D92	FLASH POINT, °F (°C)	435 (224)		460 (238)
D5949	POUR POINT, °C (°F)		-6 (21)	-12 (10)
D1500	COLOR			L4.0
D1218	REFRACTIVE INDEX @ 20°C			1.4900
D3238	n-d-M CARBON DISTRIBUTION			
	%C AROMATIC			12
	%C NAPHTHENIC			12
	%C PARAFFINIC			76
D7029	SULFUR, mg/kg			300

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

