

FEATURES & BENEFITS

- Improved processability
- Excellent solvency
- Increased durability

APPLICATIONS

Asphalt modifier; Rubber process oil for custom mixing and general rubber goods

METHOD	DESCRIPTION	TYPICAL
	LBS/GAL	8.11
D4052	API GRAVITY	14.0
D4052	SPECIFIC GRAVITY	0.973
D2501	VISCOSITY GRAVITY CONSTANT	0.915
D445	VISCOSITY @ 40°C, cSt	782.3
D445	VISCOSITY @ 100°C, cSt	25.4
D2161	VISCOSITY @ 100°F, SUS	4,410
D2161	VISCOSITY @ 210°F, SUS	127
D2270	VISCOSITY INDEX	127
D5949	POUR POINT, °C (°F)	9 (48)
D92	FLASH POINT, COC, °C (°F)	229 (445)
D1500	COLOR	D8.0
D2007	SATURATES, wt %	31.2
D2007	AROMATICS, wt %	56.3
D1218	REFRACTIVE INDEX @ 20°C	1.55721
D611	ANILINE POINT, °C	69.6
D4294	SULFUR, ppm	3,931
D4530	CARBON RESIDUE, MICRO METHOD wt %	5.5

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

