

Kenwax® Heavy Neutral Slack Wax

PROD. CODE
4454

This 135°F melt point wax is used in a variety of applications, including OSB, particleboard, MDF and hardboard manufacturing. It's also used in rust preventative compounds and in the manufacturing of firestarters and fire logs.

FEATURES & BENEFITS

- Consistent properties
- Good moisture repellency

APPLICATIONS

Rust preventatives, hardboard manufacturing, firestarters and fire logs

REGULATORY

EU REACh Registered

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
D1298B	API GRAVITY			34.5
D92	FLASH POINT, °F	500		515
D445	VISCOSITY @ 100°C, cSt	7.0	12.0	8.7
D127	MELT POINT, DROP °F	135	145	138
D721	OIL CONTENT, % WT		20	16
D1500	COLOR			D 8.0

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

