

Kenwax® Light Neutral Slack Wax

PROD. CODE
4449

This 100°F melt point wax is typically used as a sealing agent for concrete and wood products, and is also used in citronella and jar candle blends.

FEATURES & BENEFITS

- High normal paraffin content
- Excellent moisture repellency
- Consistent properties
- Low oil content

APPLICATIONS

Rust preventatives, floor sweeping compounds, jar candle blends, and sealing agent for lumber, concrete, and wood products.

REGULATORY

EU REACH Registered

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
D1298B	API GRAVITY			44.7
D97 ¹	SOLID POINT, °C	36	40	38
D721	OIL CONTENT, % WT		10.0	8.5
D92	FLASH POINT, °F COC	350		365
D445	VISCOSITY @ 100°C, cSt	2.0	2.5	2.2
D1500	COLOR, ASTM		1.0	0.5

1 - D97 Solid Point, modified to report solid point

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

