

Kenwax® Medium Neutral Slack Wax

PROD. CODE
4451

This 120°F melt point wax has a maximum oil content of 9 percent, which is a uniquely low oil content for a slack wax. It can be used in the wood board industry as a neat wax or as in emulsion form. Other applications include wood sealants and coatings, concrete sealants and metalworking applications.

FEATURES & BENEFITS

- Lowest oil content in North America
- Consistent properties
- Excellent moisture repellency

APPLICATIONS

Sealants & emulsions, undercoatings, MDF/OSB moisture repellent component, fire logs, fire starters, metalworking applications, and further processing

REGULATORY

EU REACH Registered

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
D1298B	API GRAVITY			40.9
D92	FLASH POINT, °F	410		430
D445	VISCOSITY @ 100°C, cSt	3.2	4.0	3.7
D87	MELT POINT, °F	118	125	120
D721	OIL CONTENT, %	3.0	9.0	6.0
D1500	COLOR, ASTM			L 1.0

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

