

ARGuard™ AW Hydraulic Fluids

PROD. CODE
7391, 7392, 7393

ARGuard™ AW Hydraulic Fluids are designed for hydraulic power systems typically found on mobile and stationary equipment. They are formulated with an optimum level of anti-wear technology for maximum protection against scuffing and wear in hydraulic pumps.

FEATURES & BENEFITS

- Foam inhibitors minimize both foaming and aeration issues
- Superior anti-wear properties - limits wear in pumps promoting longer componentry life and reduced operation costs
- Rust and corrosion inhibitors limit degradation of yellow metals and steel

INDUSTRY & OEM SPECIFICATIONS

- US Steel 127 and 136
- DIN 51524 Part II
- Cincinnati Machine P-68, P-69, and P-70

APPLICATIONS

ARGuard™ AW Hydraulic Fluids are most commonly used for extended oil life and pump durability, anti-wear and EP performance, good antifoam and demulsibility characteristics, excellent thermal and oxidation stability, and inhibits steel and yellow metal corrosion.

METHOD	DESCRIPTION	ISO VG		
		32 (7391)	46 (7392)	68 (7393)
D4052	API GRAVITY	31.5	31.5	31.6
CALCULATED	DENSITY, lbs/gal	7.239	7.237	7.236
D445	VISCOSITY @ 40°C, cSt	32.0	46.0	68.0
D445	VISCOSITY @ 100°C, cSt	5.4	8.0	10.9
D5949	POUR POINT, °C	-33	-45	-39
D92	FLASH POINT, °F	445	440	425
D1500	COLOR	L2.0	L2.0	L2.0

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

